



Phius Product Number: D-100206
Date Last Certified: 09/11/2025
THERM Files Available: No

Phius Certification Path: Blue Path
Valid Through: 09/11/2027
Air Leakage Test Data Available: No



PRODUCT INFORMATION

Product Name: Fibertec 750 Sliding Glass Door	
Manufacturer: Fibertec Window & Door Group	Primary Frame Material: Fiberglass
Series: 750 Series	Operation Category: Sliding Door
Model: 750 Sliding Glass Door	Operation Type: Sliding Door
NFRC CPD #: FWD-M-11-00140-00001 NFRC CPD # Lite Two: FWD-M-11-00140-00001	

IGU DETAILS

Glazing Name: 4mm-180#2-Arg95-180#4-Arg95-ClrCGI_OA 1-3/8"		
Glass Layers: Triple	Gas Fill: Argon	Spacer Model: Tremco EnerEDGE

RECOMMENDED CLIMATE ZONES (NOTE: This information is not for use in building energy models. See next section.)

Recommended Climate Zones and Whole-Door U-values by Zone, at Standard Model Size [Btu/hr·ft²·°F]

Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
Recommended Zones					✓	✓				
U-Whole-Door	0.18	0.18	0.18	0.18	0.18	0.18	0.18	0.18	0.18	0.18
Modeled Size [W × H]	78.74" × 78.74"		SHGC, Whole Door: 0.40			Condensation Resistance:				

COMPONENT-LEVEL PERFORMANCE DATA [IP Units] | Compatible with building energy modeling tools

U-COG | Center of Glass U-Values, by Climate Zone [Btu/hr·ft²·°F]

Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
U-COG Value	0.14	0.14	0.14	0.14	0.14	0.14	0.14	0.14	0.14	0.14
SHGC-COG Center of Glass Solar Heat Gain Coefficient, All Climate Zones								0.53		

Frame Parameters	Left Jamb	Right Meeting Rail	Left Head	Left Sill
Frame Section	Left	Right	Top	Bottom
Frame Width	4.25"	1.77"	4.25"	4.80"
Frame U-Value [Btu/hr·ft²·°F]	0.26	0.21	0.26	0.29
Glazing-to-Frame Psi Value [Btu/hr·ft·°F]	0.0074	0.0039	0.0072	0.0073

Frame-to-Wall Psi Value is dependent on the on-site installation condition. (See Phius Guidebook for more details.)

Frame Parameters, Lite-Two	Left Meeting Rail	Right Jamb	Right Head	Right Sill
Frame Section	Left	Right	Top	Bottom
Frame Width	4.84"	1.77"	4.84"	4.80"
Frame U-Value [Btu/hr·ft²·°F]	0.37	0.28	0.28	0.30
Glazing-to-Frame Psi Value [Btu/hr·ft·°F]	0.0125	0.0076	0.0076	0.0076

Frame-to-Wall Psi Value is dependent on the on-site installation condition. (See Phius Guidebook for more details.)

For horizontal two-lite doors, assume Lite One is on the left and Lite Two is on the right. The right jamb of Lite One is the right meeting rail. The left jamb of Lite Two is the left meeting rail. | 12/23/2025



Phius Product Number: D-100206
Date Last Certified: 09/11/2025
THERM Files Available: No

Phius Certification Path: Blue Path
Valid Through: 09/11/2027
Air Leakage Test Data Available: No



PRODUCT INFORMATION

Product Name: Fibertec 750 Sliding Glass Door	
Manufacturer: Fibertec Window & Door Group	Primary Frame Material: Fiberglass
Series: 750 Series	Operation Category: Sliding Door
Model: 750 Sliding Glass Door	Operation Type: Sliding Door
NFRC CPD #: FWD-M-11-00140-00001 NFRC CPD # Lite Two: FWD-M-11-00140-00001	

IGU DETAILS

Glazing Name: 4mm-180#2-Arg95-180#4-Arg95-ClrCGI_OA 1-3/8"		
Glass Layers: Triple	Gas Fill: Argon	Spacer Model: Tremco EnerEDGE

RECOMMENDED CLIMATE ZONES (NOTE: This information is not for use in building energy models. See next section.)

Recommended Climate Zones and Whole-Door U-values by Zone, at Standard Model Size [W/m ² K]										
Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
Recommended Zones					✓	✓				
U-Whole-Door	1.05	1.04	1.04	1.04	1.04	1.04	1.03	1.03	1.03	1.03
Modeled Size [W × H]	2.00 m × 2.00 m			SHGC, Whole Door: 0.40			Condensation Resistance:			

COMPONENT-LEVEL PERFORMANCE DATA [SI Units] | Compatible with building energy modeling tools

U-COG Center of Glass U-Values, by Climate Zone [W/m ² K]										
Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
U-COG Value	0.81	0.80	0.80	0.81	0.80	0.80	0.79	0.79	0.79	0.79
SHGC-COG Center of Glass Solar Heat Gain Coefficient, All Climate Zones								0.53		

Frame Parameters	Left Jamb	Right Meeting Rail	Left Head	Left Sill
Frame Section	Left	Right	Top	Bottom
Frame Width	108 mm	45 mm	108 mm	122 mm
Frame U-Value [W/m²K]	1.49	1.21	1.47	1.62
Glazing-to-Frame Psi Value [W/mK]	0.0129	0.0069	0.0126	0.0128

Frame-to-Wall Psi Value is dependent on the on-site installation condition. (See Phius Guidebook for more details.)

Frame Parameters, Lite-Two	Left Meeting Rail	Right Jamb	Right Head	Right Sill
Frame Section	Left	Right	Top	Bottom
Frame Width	123 mm	45 mm	123 mm	122 mm
Frame U-Value [W/m²K]	2.12	1.58	1.57	1.72
Glazing-to-Frame Psi Value [W/mK]	0.0217	0.0133	0.0132	0.0133

Frame-to-Wall Psi Value is dependent on the on-site installation condition. (See Phius Guidebook for more details.)

For horizontal two-lite doors, assume Lite One is on the left and Lite Two is on the right. The right jamb of Lite One is the right meeting rail. The left jamb of Lite Two is the left meeting rail. | 12/23/2025