



Phius Product Number: D-100210
Date Last Certified: 11/21/2025
THERM Files Available: No

Phius Certification Path: Blue Path
Valid Through: 07/27/2028
Air Leakage Test Data Available: No



PRODUCT INFORMATION

Product Name: Cascadia Universal Series Inswing Door	
Manufacturer: Cascadia Windows & Doors	Primary Frame Material: Fiberglass
Series: Universal Series	Operation Category: Swinging Door
Model: Universal Series Inswing Door	Operation Type: Single Swinging Door
NFRC CPD #: CWL-K-27-00345-00001	

IGU DETAILS

Glazing Name: E270/ Arg/ E180/ Arg/ i89(#6) (6mm) 44,0mm_CL		
Glass Layers: Triple	Gas Fill: Argon	Spacer Model: Cardinal Endur

RECOMMENDED CLIMATE ZONES (NOTE: This information is not for use in building energy models. See next section.)

Recommended Climate Zones and Whole-Door U-values by Zone, at Standard Model Size [Btu/hr·ft²·°F]										
Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
Recommended Zones	✓	✓	✓	✓	✓	✓	✓			
U-Whole-Door	0.13	0.14	0.14	0.14	0.14	0.14	0.14	0.14	0.14	0.14
Modeled Size [W × H]	37.80" × 82.28"			SHGC, Whole Door: 0.19			Condensation Resistance:			

COMPONENT-LEVEL PERFORMANCE DATA [IP Units] | Compatible with building energy modeling tools

U-COG Center of Glass U-Values, by Climate Zone [Btu/hr·ft²·°F]										
Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
U-COG Value	0.10	0.11	0.11	0.11	0.11	0.11	0.11	0.11	0.11	0.11
SHGC-COG Center of Glass Solar Heat Gain Coefficient, All Climate Zones								0.30		

Frame Parameters	Left Jamb	Right Jamb	Left Head	Sill
Frame Section	Left	Right	Top	Bottom
Frame Width	5.20"	5.20"	5.20"	5.75"
Frame U-Value [Btu/hr·ft²·°F]	0.18	0.18	0.17	0.18
Glazing-to-Frame Psi Value [Btu/hr·ft·°F]	0.0042	0.0042	0.0040	0.0041
Frame-to-Wall Psi Value is dependent on the on-site installation condition. (See Phius Guidebook for more details.)				



Phius Product Number: D-100210
Date Last Certified: 11/21/2025
THERM Files Available: No

Phius Certification Path: Blue Path
Valid Through: 07/27/2028
Air Leakage Test Data Available: No



PRODUCT INFORMATION

Product Name: Cascadia Universal Series Inswing Door	
Manufacturer: Cascadia Windows & Doors	Primary Frame Material: Fiberglass
Series: Universal Series	Operation Category: Swinging Door
Model: Universal Series Inswing Door	Operation Type: Single Swinging Door
NFRC CPD #: CWL-K-27-00345-00001	

IGU DETAILS

Glazing Name: E270/ Arg/ E180/ Arg/ i89(#6) (6mm) 44,0mm_CL		
Glass Layers: Triple	Gas Fill: Argon	Spacer Model: Cardinal Endur

RECOMMENDED CLIMATE ZONES *(NOTE: This information is not for use in building energy models. See next section.)*

Recommended Climate Zones and Whole-Door U-values by Zone, at Standard Model Size [W/m ² K]										
Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
Recommended Zones	✓	✓	✓	✓	✓	✓	✓			
U-Whole-Door	0.74	0.77	0.77	0.77	0.77	0.77	0.77	0.77	0.78	0.79
Modeled Size [W × H]	0.96 m × 2.09 m		SHGC, Whole Door: 0.19				Condensation Resistance:			

COMPONENT-LEVEL PERFORMANCE DATA [SI Units] | *Compatible with building energy modeling tools*

U-COG Center of Glass U-Values, by Climate Zone [W/m ² K]										
Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
U-COG Value	0.57	0.60	0.60	0.60	0.61	0.61	0.61	0.61	0.62	0.63
SHGC-COG Center of Glass Solar Heat Gain Coefficient, All Climate Zones								0.30		

Frame Parameters	Left Jamb	Right Jamb	Left Head	Sill
Frame Section	Left	Right	Top	Bottom
Frame Width	132 mm	132 mm	132 mm	146 mm
Frame U-Value [W/m²K]	1.00	1.00	0.98	1.01
Glazing-to-Frame Psi Value [W/mK]	0.0074	0.0074	0.007	0.0071
Frame-to-Wall Psi Value is dependent on the on-site installation condition. <i>(See Phius Guidebook for more details.)</i>				