



Phius Product Number: D-100214
Date Last Certified: 11/21/2025
THERM Files Available: No

Phius Certification Path: Blue Path
Valid Through: 05/29/2029
Air Leakage Test Data Available: No



PRODUCT INFORMATION

Product Name: Cascadia Universal Series Tilt Slide Door	
Manufacturer: Cascadia Windows & Doors	Primary Frame Material: Fiberglass
Series: Universal Series	Operation Category: Sliding Door
Model: Universal Series Tilt Slide Door	Operation Type: 0
NFRC CPD #: CWL-K-28-00089-00001	

IGU DETAILS

Glazing Name: E270/ARG90/E180/ARG90/i89 (6MM/6MM/6MM) 44MM IG_CL		
Glass Layers: Triple	Gas Fill: Argon	Spacer Model: Cardinal Endur

RECOMMENDED CLIMATE ZONES (NOTE: This information is not for use in building energy models. See next section.)

Recommended Climate Zones and Whole-Door U-values by Zone, at Standard Model Size [Btu/hr·ft²·°F]										
Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
Recommended Zones	✓	✓	✓	✓	✓	✓	✓			
U-Whole-Door	0.14	0.14	0.14	0.14	0.14	0.14	0.14	0.14	0.14	0.14
Modeled Size [W × H]	78.74" × 78.74"				SHGC, Whole Door: 0.19			Condensation Resistance:		

COMPONENT-LEVEL PERFORMANCE DATA [IP Units] | Compatible with building energy modeling tools

U-COG Center of Glass U-Values, by Climate Zone [Btu/hr·ft²·°F]										
Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
U-COG Value	0.10	0.11	0.11	0.11	0.11	0.11	0.11	0.11	0.11	0.11
SHGC-COG Center of Glass Solar Heat Gain Coefficient, All Climate Zones								0.30		

Frame Parameters	Left Jamb	Right Meeting Rail	Left Head	Left Sill
Frame Section	Left	Right	Top	Bottom
Frame Width	5.75"	7.36"	6.65"	6.65"
Frame U-Value [Btu/hr·ft²·°F]	0.17	0.19	0.17	0.18
Glazing-to-Frame Psi Value [Btu/hr·ft²·°F]	0.0038	0.0036	0.0033	0.0034

Frame-to-Wall Psi Value is dependent on the on-site installation condition. (See Phius Guidebook for more details.)

Frame Parameters, Lite-Two	Left Meeting Rail	Right Jamb	Right Head	Right Sill
Frame Section	Left	Right	Top	Bottom
Frame Width	2.28"	7.36"	3.19"	3.19"
Frame U-Value [Btu/hr·ft²·°F]	0.19	0.22	0.22	0.21
Glazing-to-Frame Psi Value [Btu/hr·ft²·°F]	0.0036	0.0037	0.0007	0.0012

Frame-to-Wall Psi Value is dependent on the on-site installation condition. (See Phius Guidebook for more details.)

For horizontal two-lite doors, assume Lite One is on the left and Lite Two is on the right. The right jamb of Lite One is the right meeting rail. The left jamb of Lite Two is the left meeting rail. | 12/23/2025



Phius Product Number: D-100214
Date Last Certified: 11/21/2025
THERM Files Available: No

Phius Certification Path: Blue Path
Valid Through: 05/29/2029
Air Leakage Test Data Available: No



PRODUCT INFORMATION

Product Name: Cascadia Universal Series Tilt Slide Door	
Manufacturer: Cascadia Windows & Doors	Primary Frame Material: Fiberglass
Series: Universal Series	Operation Category: Sliding Door
Model: Universal Series Tilt Slide Door	Operation Type: 0
NFRC CPD #: CWL-K-28-00089-00001	

IGU DETAILS

Glazing Name: E270/ARG90/E180/ARG90/i89 (6MM/6MM/6MM) 44MM IG_CL		
Glass Layers: Triple	Gas Fill: Argon	Spacer Model: Cardinal Endur

RECOMMENDED CLIMATE ZONES (NOTE: This information is not for use in building energy models. See next section.)

Recommended Climate Zones and Whole-Door U-values by Zone, at Standard Model Size [W/m²K]										
Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
Recommended Zones	✓	✓	✓	✓	✓	✓	✓			
U-Whole-Door	0.78	0.80	0.80	0.80	0.80	0.80	0.80	0.80	0.81	0.82
Modeled Size [W × H]	2.00 m × 2.00 m		SHGC, Whole Door: 0.19				Condensation Resistance:			

COMPONENT-LEVEL PERFORMANCE DATA [SI Units] | Compatible with building energy modeling tools

U-COG Center of Glass U-Values, by Climate Zone [W/m²K]										
Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
U-COG Value	0.57	0.61	0.61	0.61	0.61	0.61	0.62	0.62	0.63	0.64
SHGC-COG Center of Glass Solar Heat Gain Coefficient, All Climate Zones								0.30		

Frame Parameters	Left Jamb	Right Meeting Rail	Left Head	Left Sill
Frame Section	Left	Right	Top	Bottom
Frame Width	146 mm	187 mm	169 mm	169 mm
Frame U-Value [W/m²K]	0.97	1.08	0.98	1.04
Glazing-to-Frame Psi Value [W/mK]	0.0066	0.0064	0.0058	0.006

Frame-to-Wall Psi Value is dependent on the on-site installation condition. (See Phius Guidebook for more details.)

Frame Parameters, Lite-Two	Left Meeting Rail	Right Jamb	Right Head	Right Sill
Frame Section	Left	Right	Top	Bottom
Frame Width	58 mm	187 mm	81 mm	81 mm
Frame U-Value [W/m²K]	1.08	1.26	1.26	1.21
Glazing-to-Frame Psi Value [W/mK]	0.0064	0.0065	0.0013	0.0021

Frame-to-Wall Psi Value is dependent on the on-site installation condition. (See Phius Guidebook for more details.)

For horizontal two-lite doors, assume Lite One is on the left and Lite Two is on the right. The right jamb of Lite One is the right meeting rail. The left jamb of Lite Two is the left meeting rail. | 12/23/2025