



Phius Product Number: D-100272
Date Last Certified: 02/25/2026
THERM Files Available: No

Phius Certification Path: Blue Path
Valid Through: 02/25/2028
Air Leakage Test Data Available: No



PRODUCT INFORMATION

Product Name: Inline 600 Series Sliding Glass Door	
Manufacturer: Inline Fiberglass Ltd	Primary Frame Material: Fiberglass
Series: 600 Series	Operation Category: Sliding Door
Model: 600 Series Sliding Glass Door	Operation Type: Sliding Door
NFRC CPD #: IFL-A-26-00111-00001	

IGU DETAILS

Glazing Name: 4MM 272 ARG 4MM CL ARG 180 4MM - 1 7/16" IG		
Glass Layers: Triple	Gas Fill: Argon	Spacer Model: Cardinal Endur

RECOMMENDED CLIMATE ZONES (NOTE: This information is not for use in building energy models. See next section.)

Recommended Climate Zones and Whole-Door U-values by Zone, at Standard Model Size [Btu/hr·ft ² ·°F]										
Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
Recommended Zones				✓	✓	✓				
U-Whole-Door	0.19	0.19	0.19	0.19	0.19	0.19	0.19	0.19	0.19	0.19
Modeled Size [W × H]	78.74" × 78.74"			SHGC, Whole Door: 0.28			Condensation Resistance:			

COMPONENT-LEVEL PERFORMANCE DATA [IP Units] | Compatible with building energy modeling tools

U-COG Center of Glass U-Values, by Climate Zone [Btu/hr·ft ² ·°F]										
Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
U-COG Value	0.13	0.13	0.13	0.13	0.13	0.13	0.13	0.13	0.13	0.13
SHGC-COG Center of Glass Solar Heat Gain Coefficient, All Climate Zones								0.37		

Frame Parameters	Left Jamb	Right Meeting Rail	Left Head	Left Sill
Frame Section	Left	Right	Top	Bottom
Frame Width	4.06"	1.38"	4.37"	4.45"
Frame U-Value [Btu/hr·ft ² ·°F]	0.33	0.43	0.33	0.33
Glazing-to-Frame Psi Value [Btu/hr·ft ² ·°F]	0.0119	0.0179	0.0111	0.0111

Frame-to-Wall Psi Value is dependent on the on-site installation condition. (See Phius Guidebook for more details.)

Frame Parameters, Lite-Two	Left Meeting Rail	Right Jamb	Right Head	Right Sill
Frame Section	Left	Right	Top	Bottom
Frame Width	4.25"	1.38"	4.37"	4.45"
Frame U-Value [Btu/hr·ft ² ·°F]	0.26	0.33	0.30	0.39
Glazing-to-Frame Psi Value [Btu/hr·ft ² ·°F]	0.0077	0.0120	0.0109	0.0110

Frame-to-Wall Psi Value is dependent on the on-site installation condition. (See Phius Guidebook for more details.)

For horizontal two-lite doors, assume Lite One is on the left and Lite Two is on the right. The right jamb of Lite One is the right meeting rail. The left jamb of Lite Two is the left meeting rail. | 02/25/2026



Phius Product Number: D-100272
Date Last Certified: 02/25/2026
THERM Files Available: No

Phius Certification Path: Blue Path
Valid Through: 02/25/2028
Air Leakage Test Data Available: No



PRODUCT INFORMATION

Product Name: Inline 600 Series Sliding Glass Door	
Manufacturer: Inline Fiberglass Ltd	Primary Frame Material: Fiberglass
Series: 600 Series	Operation Category: Sliding Door
Model: 600 Series Sliding Glass Door	Operation Type: Sliding Door
NFRC CPD #: IFL-A-26-00111-00001	

IGU DETAILS

Glazing Name: 4MM 272 ARG 4MM CL ARG 180 4MM - 1 7/16" IG		
Glass Layers: Triple	Gas Fill: Argon	Spacer Model: Cardinal Endur

RECOMMENDED CLIMATE ZONES (NOTE: This information is not for use in building energy models. See next section.)

Recommended Climate Zones and Whole-Door U-values by Zone, at Standard Model Size [W/m ² K]										
Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
Recommended Zones				✓	✓	✓				
U-Whole-Door	1.08	1.08	1.08	1.08	1.08	1.08	1.07	1.07	1.08	1.08
Modeled Size [W × H]	2.00 m × 2.00 m		SHGC, Whole Door: 0.28			Condensation Resistance:				

COMPONENT-LEVEL PERFORMANCE DATA [SI Units] | Compatible with building energy modeling tools

U-COG Center of Glass U-Values, by Climate Zone [W/m ² K]										
Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
U-COG Value	0.76	0.75	0.75	0.75	0.75	0.75	0.74	0.74	0.75	0.75
SHGC-COG Center of Glass Solar Heat Gain Coefficient, All Climate Zones								0.37		

Frame Parameters	Left Jamb	Right Meeting Rail	Left Head	Left Sill
Frame Section	Left	Right	Top	Bottom
Frame Width	103 mm	35 mm	111 mm	113 mm
Frame U-Value [W/m ² K]	1.88	2.42	1.89	1.86
Glazing-to-Frame Psi Value [W/mK]	0.0207	0.0311	0.0193	0.0193

Frame-to-Wall Psi Value is dependent on the on-site installation condition. (See Phius Guidebook for more details.)

Frame Parameters, Lite-Two	Left Meeting Rail	Right Jamb	Right Head	Right Sill
Frame Section	Left	Right	Top	Bottom
Frame Width	108 mm	35 mm	111 mm	113 mm
Frame U-Value [W/m ² K]	1.50	1.90	1.68	2.20
Glazing-to-Frame Psi Value [W/mK]	0.0134	0.0208	0.0189	0.0191

Frame-to-Wall Psi Value is dependent on the on-site installation condition. (See Phius Guidebook for more details.)

For horizontal two-lite doors, assume Lite One is on the left and Lite Two is on the right. The right jamb of Lite One is the right meeting rail. The left jamb of Lite Two is the left meeting rail. | 02/25/2026