



Phius Product Number: W-101365
Date Last Certified: 08/15/2023
THERM Files Available: No

Phius Certification Path: Blue Path
Valid Through: 08/15/2025
Air Leakage Test Data Available: No



PRODUCT INFORMATION

Product Name: Drutex I5 Casement	
Manufacturer: DRUTEX S A	Primary Frame Material: Vinyl
Series: I5	Fixed or Operable: Operable
Model: I5 Casement	Operation Type: Casement
NFRC CPD #: DRU-K-3-00005-00001	

IGU DETAILS

Glazing Name: CG PREMIUM 2 / ARG90 / CLR-LAMI (6MM/6MM 6x015 PVB 6MM) - 38MM IG_CL		
Glass Layers: Double	Gas Fill: Argon	Spacer: Saint Gobain SWISSPACER

RECOMMENDED CLIMATE ZONES (NOTE: This information is not for use in building energy models. See next section.)

Recommended Climate Zones and Whole-Window U-values by Zone, at Standard Model Size [Btu/hr·ft²·°F]										
Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
Recommended Zones				✓						
U-Whole-Window	0.23	0.25	0.25	0.24	0.26	0.25	0.26	0.26	0.27	0.28
Modeled Size [W×H]	23.62" × 59.06"		SHGC, Whole Window: 0.27				Condensation Resistance:			

COMPONENT-LEVEL PERFORMANCE DATA [IP Units] | Compatible with building energy modeling tools

U-COG Center of Glass U-Values, by Climate Zone [Btu/hr·ft²·°F]										
Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
U-COG Value	0.16	0.19	0.19	0.18	0.21	0.20	0.22	0.22	0.24	0.26
SHGC-COG Center of Glass Solar Heat Gain Coefficient, All Climate Zones								0.56		

Frame Parameters	Left Jamb	Right Jamb	Head	Sill
Frame Section	Left	Right	Top	Bottom
Frame Width	4.88"	4.88"	4.88"	4.88"
Frame U-Value [Btu/hr·ft²·°F]	0.28	0.28	0.28	0.28
Glazing-to-Frame Psi Value [Btu/hr·ft·°F]	0.0087	0.0087	0.0079	0.0079
Frame-to-Wall Psi Value is dependent on the on-site installation condition. (See Phius Guidebook for more details.)				



Phius Product Number: W-101365
Date Last Certified: 08/15/2023
THERM Files Available: No

Phius Certification Path: Blue Path
Valid Through: 08/15/2025
Air Leakage Test Data Available: No



PRODUCT INFORMATION

Product Name: Drutex I5 Casement	
Manufacturer: DRUTEX S A	Primary Frame Material: Vinyl
Series: I5	Fixed or Operable: Operable
Model: I5 Casement	Operation Type: Casement
NFRC CPD #: DRU-K-3-00005-00001	

IGU DETAILS

Glazing Name: CG PREMIUM 2 / ARG90 / CLR-LAMI (6MM/6MM 6x015 PVB 6MM) - 38MM IG_CL		
Glass Layers: Double	Gas Fill: Argon	Spacer: Saint Gobain SWISSPACER

RECOMMENDED CLIMATE ZONES (NOTE: This information is not for use in building energy models. See next section.)

Recommended Climate Zones and Whole-Window U-values by Zone, at Standard Model Size [W/m²K]										
Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
Recommended Zones				✓						
U-Whole-Window	1.31	1.40	1.40	1.37	1.45	1.42	1.48	1.50	1.55	1.58
Modeled Size [W × H]	0.60 m × 1.50 m		SHGC, Whole Window: 0.27				Condensation Resistance:			

COMPONENT-LEVEL PERFORMANCE DATA [SI Units] | Compatible with building energy modeling tools

U-COG Center of Glass U-Values, by Climate Zone [W/m²K]										
Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
U-COG Value	0.90	1.09	1.09	1.02	1.18	1.13	1.25	1.28	1.38	1.45
SHGC-COG Center of Glass Solar Heat Gain Coefficient, All Climate Zones								0.56		

Frame Parameters	Left Jamb	Right Jamb	Head	Sill
Frame Section	Left	Right	Top	Bottom
Frame Width	124 mm	124 mm	124 mm	124 mm
Frame U-Value [W/m²K]	1.62	1.62	1.59	1.59
Glazing-to-Frame Psi Value [W/mK]	0.0152	0.0152	0.0137	0.0137
Frame-to-Wall Psi Value is dependent on the on-site installation condition. (See Phius Guidebook for more details.)				