



Phius Product Number: W-101469
Date Last Certified: 08/15/2023
THERM Files Available: No

Phius Certification Path: Blue Path
Valid Through: 08/15/2025
Air Leakage Test Data Available: No



PRODUCT INFORMATION

Product Name: Eurotek 70 Tilt Turn Window	
Manufacturer: Value Windows & Doors	Primary Frame Material: Vinyl
Series: Eurotek 70	Fixed or Operable: Operable
Model: 70 Tilt Turn Window	Operation Type: Dual Action Tilt Turn
NFRC CPD #: VWS-A-53-00019-00001	

IGU DETAILS

Glazing Name: E366 / Arg / Clr / Arg / E366 - 39.5mm (5mm-5mm-5mm)_CL		
Glass Layers: Triple	Gas Fill: Argon	Spacer: Quanex Super Spacer

RECOMMENDED CLIMATE ZONES (NOTE: This information is not for use in building energy models. See next section.)

Recommended Climate Zones and Whole-Window U-values by Zone, at Standard Model Size [Btu/hr·ft ² ·°F]										
Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
Recommended Zones	✓	✓	✓	✓	✓	✓				
U-Whole-Window	0.17	0.17	0.17	0.17	0.17	0.17	0.17	0.17	0.17	0.17
Modeled Size [W×H]	47.24" × 59.06"		SHGC, Whole Window: 0.16				Condensation Resistance:			

COMPONENT-LEVEL PERFORMANCE DATA [IP Units] | Compatible with building energy modeling tools

U-COG Center of Glass U-Values, by Climate Zone [Btu/hr·ft ² ·°F]										
Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
U-COG Value	0.12	0.12	0.12	0.12	0.12	0.12	0.12	0.12	0.12	0.12
SHGC-COG Center of Glass Solar Heat Gain Coefficient, All Climate Zones								0.23		

Frame Parameters	Left Jamb	Right Jamb	Head	Sill
Frame Section	Left	Right	Top	Bottom
Frame Width	4.72"	4.72"	4.72"	4.72"
Frame U-Value [Btu/hr·ft²·°F]	0.27	0.27	0.27	0.27
Glazing-to-Frame Psi Value [Btu/hr·ft·°F]	0.0102	0.0102	0.0098	0.0097
Frame-to-Wall Psi Value is dependent on the on-site installation condition. (See Phius Guidebook for more details.)				



Phius Product Number: W-101469
Date Last Certified: 08/15/2023
THERM Files Available: No

Phius Certification Path: Blue Path
Valid Through: 08/15/2025
Air Leakage Test Data Available: No



PRODUCT INFORMATION

Product Name: Eurotek 70 Tilt Turn Window	
Manufacturer: Value Windows & Doors	Primary Frame Material: Vinyl
Series: Eurotek 70	Fixed or Operable: Operable
Model: 70 Tilt Turn Window	Operation Type: Dual Action Tilt Turn
NFRC CPD #: VWS-A-53-00019-00001	

IGU DETAILS

Glazing Name: E366 / Arg /Clr / Arg / E366 - 39.5mm (5mm-5mm-5mm)_CL		
Glass Layers: Triple	Gas Fill: Argon	Spacer: Quanex Super Spacer

RECOMMENDED CLIMATE ZONES (NOTE: This information is not for use in building energy models. See next section.)

Recommended Climate Zones and Whole-Window U-values by Zone, at Standard Model Size [W/m²K]										
Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
Recommended Zones	✓	✓	✓	✓	✓	✓				
U-Whole-Window	0.98	0.98	0.98	0.98	0.98	0.98	0.98	0.98	0.99	0.99
Modeled Size [W × H]	1.20 m × 1.50 m		SHGC, Whole Window: 0.16				Condensation Resistance:			

COMPONENT-LEVEL PERFORMANCE DATA [SI Units] | Compatible with building energy modeling tools

U-COG Center of Glass U-Values, by Climate Zone [W/m²K]										
Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
U-COG Value	0.66	0.66	0.66	0.66	0.65	0.65	0.65	0.65	0.66	0.67
SHGC-COG Center of Glass Solar Heat Gain Coefficient, All Climate Zones								0.23		

Frame Parameters	Left Jamb	Right Jamb	Head	Sill
Frame Section	Left	Right	Top	Bottom
Frame Width	120 mm	120 mm	120 mm	120 mm
Frame U-Value [W/m²K]	1.52	1.52	1.52	1.52
Glazing-to-Frame Psi Value [W/mK]	0.0178	0.0178	0.017	0.0168
Frame-to-Wall Psi Value is dependent on the on-site installation condition. (See Phius Guidebook for more details.)				