



Phius Product Number: W-101566
Date Last Certified: 08/15/2023
THERM Files Available: No

Phius Certification Path: Orange Path
Valid Through: 08/15/2025
Air Leakage Test Data Available: No



PRODUCT INFORMATION		
Product Name: Ventana Series 86 Fixed Option 200		
Manufacturer: Ventana USA	Primary Frame Material: Vinyl	
Series: Series 86	Fixed or Operable: Fixed	
Model: Series 86 Fixed Option 200	Operation Type: Fixed	
IGU DETAILS		
Glazing Name: 3mm LoE 272#2 / 12.7mm / 3mm Clear / 12.7mm / 3mm LoE 272#5		
Glass Layers: Triple	Gas Fill: Argon	Spacer: Cardinal Endur

RECOMMENDED CLIMATE ZONES <i>(NOTE: This information is not for use in building energy models. See next section.)</i>										
Recommended Climate Zones and Whole-Window U-values by Zone, at Standard Model Size [Btu/hr·ft ² ·°F]										
Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
Recommended Zones				✓	✓	✓	✓			
U-Whole-Window	0.15	0.15	0.15	0.15	0.14	0.14	0.14	0.14	0.14	0.14
Modeled Size [W×H]	47.24" × 59.06"			SHGC, Whole Window: 0.28			Condensation Resistance:			

COMPONENT-LEVEL PERFORMANCE DATA [IP Units] | Compatible with building energy modeling tools

U-COG Center of Glass U-Values, by Climate Zone [Btu/hr·ft ² ·°F]										
Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
U-COG Value	0.12	0.12	0.12	0.12	0.12	0.12	0.12	0.12	0.12	0.12
SHGC-COG Center of Glass Solar Heat Gain Coefficient, All Climate Zones								0.35		

Frame Parameters	Left Jamb	Right Jamb	Head	Sill
Frame Section	Left	Right	Top	Bottom
Frame Width	2.91"	2.91"	2.91"	2.91"
Frame U-Value [Btu/hr·ft²·°F]	0.17	0.17	0.17	0.17
Glazing-to-Frame Psi Value [Btu/hr·ft²·°F]	0.0161	0.0161	0.0160	0.0161

Frame-to-Wall Psi Value is dependent on the on-site installation condition. *(See Phius Guidebook for more details.)*



Phius Product Number: W-101566
Date Last Certified: 08/15/2023
THERM Files Available: No

Phius Certification Path: Orange Path
Valid Through: 08/15/2025
Air Leakage Test Data Available: No



PRODUCT INFORMATION

Product Name: Ventana Series 86 Fixed Option 200	
Manufacturer: Ventana USA	Primary Frame Material: Vinyl
Series: Series 86	Fixed or Operable: Fixed
Model: Series 86 Fixed Option 200	Operation Type: Fixed

IGU DETAILS

Glazing Name: 3mm LoE 272#2 / 12.7mm / 3mm Clear / 12.7mm / 3mm LoE 272#5		
Glass Layers: Triple	Gas Fill: Argon	Spacer: Cardinal Endur

RECOMMENDED CLIMATE ZONES *(NOTE: This information is not for use in building energy models. See next section.)*

Recommended Climate Zones and Whole-Window U-values by Zone, at Standard Model Size [W/m²K]										
Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
Recommended Zones				✓	✓	✓	✓			
U-Whole-Window	0.84	0.82	0.82	0.83	0.82	0.82	0.82	0.82	0.82	0.82
Modeled Size [W x H]	1.20 m x 1.50 m		SHGC, Whole Window: 0.28				Condensation Resistance:			

COMPONENT-LEVEL PERFORMANCE DATA [SI Units] | *Compatible with building energy modeling tools*

U-COG Center of Glass U-Values, by Climate Zone [W/m²K]										
Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
U-COG Value	0.70	0.69	0.69	0.69	0.68	0.68	0.68	0.68	0.68	0.68
SHGC-COG Center of Glass Solar Heat Gain Coefficient, All Climate Zones								0.35		

Frame Parameters	Left Jamb	Right Jamb	Head	Sill
Frame Section	Left	Right	Top	Bottom
Frame Width	74 mm	74 mm	74 mm	74 mm
Frame U-Value [W/m ² K]	0.99	0.99	0.99	0.98
Glazing-to-Frame Psi Value [W/mK]	0.0279	0.0279	0.0277	0.0279

Frame-to-Wall Psi Value is dependent on the on-site installation condition. *(See Phius Guidebook for more details.)*