



Phius Product Number: W-102026
Date Last Certified: 06/06/2024
THERM Files Available: No

Phius Certification Path: Blue Path
Valid Through: 06/06/2026
Air Leakage Test Data Available: No



PRODUCT INFORMATION

Product Name: DRUTEX IGLO ENERGY Classic Fixed & Tilt & Turn

Manufacturer: DRUTEX S A

Primary Frame Material: Vinyl

Series: IGLO ENERGY Classic

Fixed or Operable: Combination

Model: IGLO ENERGY Classic Fixed + Tilt & Turn

Operation Type: Combination Unit

Number of Lites: Two-Lite

Two-Lite Orientation: Horizontal

NFRC CPD #: DRU-K-5-00292-00001 | **NFRC CPD # Lite Two:** DRU-K-6-00292-00001

IGU DETAILS

Glazing Name: CG Premium 2 / ARG90 / Extra CLR / ARG90 / CG Premium 2 (4mm | 4x015PVB | 4mm/4mm/4mm)

Glass Layers: Triple

Gas Fill: Argon

Spacer: SWISSPACER ULTIMATE

RECOMMENDED CLIMATE ZONES (NOTE: This information is not for use in building energy models. See next section.)

Recommended Climate Zones and Whole-Window U-values by Zone, at Standard Model Size [Btu/hr·ft²·°F]

Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
Recommended Zones					✓	✓	✓			
U-Whole-Window	0.15	0.15	0.15	0.15	0.15	0.15	0.15	0.15	0.16	0.16

Modeled Size [W×H]

94.49" × 59.06"

SHGC, Whole Window: 0.31

Condensation Resistance:

COMPONENT-LEVEL PERFORMANCE DATA [IP Units] | *Compatible with building energy modeling tools*

U-COG | Center of Glass U-Values, by Climate Zone [Btu/hr·ft²·°F]

Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
U-COG Value	0.11	0.11	0.11	0.11	0.11	0.11	0.11	0.11	0.12	0.12

SHGC-COG | Center of Glass Solar Heat Gain Coefficient, All Climate Zones

0.45

Frame Parameters	Left Jamb	Right Meeting Rail	Left Head	Left Sill
Frame Section	Left	Right	Top	Bottom
Frame Width	2.95"	5.94"	2.95"	2.95"
Frame U-Value [Btu/hr·ft ² ·°F]	0.23	0.24	0.22	0.22
Glazing-to-Frame Psi Value [Btu/hr·ft ² ·°F]	0.0072	0.0074	0.0063	0.0063

Frame-to-Wall Psi Value is dependent on the on-site installation condition. (See Phius Guidebook for more details.)

Frame Parameters, Lite-Two	Left Meeting Rail	Right Jamb	Right Head	Right Sill
Frame Section	Left	Right	Top	Bottom
Frame Width	5.94"	4.92"	4.92"	4.92"
Frame U-Value [Btu/hr·ft ² ·°F]	0.24	0.23	0.23	0.23
Glazing-to-Frame Psi Value [Btu/hr·ft ² ·°F]	0.0074	0.0068	0.0068	0.0068

Frame-to-Wall Psi Value is dependent on the on-site installation condition. (See Phius Guidebook for more details.)

For horizontal two-lite products, assume Lite One is on the left and Lite Two is on the right. The right jamb of Lite One is the right meeting rail. The left jamb of Lite Two is the left meeting rail. | 06/06/2024



PhiUS Product Number: W-102026
Date Last Certified: 06/06/2024
THERM Files Available: No

PhiUS Certification Path: Blue Path
Valid Through: 06/06/2026
Air Leakage Test Data Available: No



PRODUCT INFORMATION

Product Name: DRUTEX IGLO ENERGY Classic Fixed & Tilt & Turn

Manufacturer: DRUTEX S A

Primary Frame Material: Vinyl

Series: IGLO ENERGY Classic

Fixed or Operable: Combination

Model: IGLO ENERGY Classic Fixed + Tilt & Turn

Operation Type: Combination Unit

Number of Lites: Two-Lite

Two-Lite Orientation: Horizontal

NFRC CPD #: DRU-K-5-00292-00001 | **NFRC CPD # Lite Two:** DRU-K-6-00292-00001

IGU DETAILS

Glazing Name: CG Premium 2 / ARG90 / Extra CLR / ARG90 / CG Premium 2 (4mm | 4x015PVB | 4mm/4mm/4mm)

Glass Layers: Triple

Gas Fill: Argon

Spacer: SWISSPACER ULTIMATE

RECOMMENDED CLIMATE ZONES (NOTE: This information is not for use in building energy models. See next section.)

Recommended Climate Zones and Whole-Window U-values by Zone, at Standard Model Size [W/m²K]

Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
Recommended Zones					✓	✓	✓			
U-Whole-Window	0.87	0.87	0.87	0.87	0.87	0.87	0.88	0.88	0.90	0.92

Modeled Size [W × H] 2.40 m × 1.50 m

SHGC, Whole Window: 0.31

Condensation Resistance:

COMPONENT-LEVEL PERFORMANCE DATA [SI Units] | *Compatible with building energy modeling tools*

U-COG | Center of Glass U-Values, by Climate Zone [W/m²K]

Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
U-COG Value	0.62	0.62	0.62	0.62	0.62	0.62	0.63	0.63	0.66	0.69

SHGC-COG | Center of Glass Solar Heat Gain Coefficient, All Climate Zones

0.45

Frame Parameters	Left Jamb	Right Meeting Rail	Left Head	Left Sill
Frame Section	Left	Right	Top	Bottom
Frame Width	75 mm	151 mm	75 mm	75 mm
Frame U-Value [W/m ² K]	1.32	1.36	1.23	1.23
Glazing-to-Frame Psi Value [W/mK]	0.0125	0.0129	0.011	0.011

Frame-to-Wall Psi Value is dependent on the on-site installation condition. (See *PhiUS Guidebook* for more details.)

Frame Parameters, Lite-Two	Left Meeting Rail	Right Jamb	Right Head	Right Sill
Frame Section	Left	Right	Top	Bottom
Frame Width	151 mm	125 mm	125 mm	125 mm
Frame U-Value [W/m ² K]	1.36	1.32	1.33	1.33
Glazing-to-Frame Psi Value [W/mK]	0.0129	0.0118	0.0118	0.0118

Frame-to-Wall Psi Value is dependent on the on-site installation condition. (See *PhiUS Guidebook* for more details.)

For horizontal two-lite products, assume Lite One is on the left and Lite Two is on the right. The right jamb of Lite One is the right meeting rail. The left jamb of Lite Two is the left meeting rail. | 06/06/2024