



**Phius Product Number:** W-102029  
**Date Last Certified:** 08/28/2025  
**THERM Files Available:** No

**Phius Certification Path:** Blue Path  
**Valid Through:** 08/24/2026  
**Air Leakage Test Data Available:** No



**PRODUCT INFORMATION**

<b>Product Name:</b> DRUTEX IGLO ENERGY Classic Tilt & Turn Over Fixed	
<b>Manufacturer:</b> DRUTEX S A	<b>Primary Frame Material:</b> Vinyl
<b>Series:</b> IGLO ENERGY Classic	<b>Fixed or Operable:</b> Combination
<b>Model:</b> IGLO ENERGY Classic Tilt & Turn over Fixed	<b>Operation Type:</b> Combination Unit
<b>Number of Lites:</b> Two-Lite	<b>Two-Lite Orientation:</b> Vertical
<b>NFRC CPD #:</b> DRU-K-6-00262-00001   <b>NFRC CPD # Lite Two:</b> DRU-K-5-00252-00001	

**IGU DETAILS**

<b>Glazing Name:</b> SGG Cool-Lite SKN176 / ARG90 / SGG PlaniClear / ARG90 / SGG PlaniTherm XN (6mm/4mm/4mm)		
<b>Glass Layers:</b> Triple	<b>Gas Fill:</b> Argon	<b>Spacer:</b> SWISSPACER ULTIMATE

**RECOMMENDED CLIMATE ZONES** (NOTE: This information is not for use in building energy models. See next section.)

<b>Recommended Climate Zones and Whole-Window U-values by Zone, at Standard Model Size [Btu/hr·ft²·°F]</b>										
Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
Recommended Zones	✓	✓	✓	✓	✓	✓				
U-Whole-Window	0.16	0.16	0.16	0.16	0.16	0.16	0.16	0.16	0.17	0.17
Modeled Size [W×H]	47.24" × 119.11"		SHGC, Whole Window: 0.19				Condensation Resistance:			

**COMPONENT-LEVEL PERFORMANCE DATA [IP Units]** | Compatible with building energy modeling tools

<b>U-COG   Center of Glass U-Values, by Climate Zone [Btu/hr·ft²·°F]</b>										
Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
U-COG Value	0.10	0.10	0.10	0.10	0.10	0.10	0.11	0.11	0.12	0.13
<b>SHGC-COG   Center of Glass Solar Heat Gain Coefficient, All Climate Zones</b>								0.31		

Frame Parameters	Upper Left Jamb	Upper Right Jamb	Head	Upper Meeting Rail
Frame Section	Left	Right	Top	Bottom
Frame Width	4.92"	4.92"	4.92"	5.94"
Frame U-Value [Btu/hr·ft²·°F]	0.23	0.23	0.23	0.23
Glazing-to-Frame Psi Value [Btu/hr·ft·°F]	0.0067	0.0067	0.0057	0.0059

**Frame-to-Wall Psi Value** is dependent on the on-site installation condition. (See Phius Guidebook for more details.)

Frame Parameters, Lite-Two	Lower Left Jamb	Lower Right Jamb	Lower Meeting Rail	Sill
Frame Section	Left	Right	Top	Bottom
Frame Width	2.95"	2.95"	5.94"	2.95"
Frame U-Value [Btu/hr·ft²·°F]	0.23	0.23	0.23	0.21
Glazing-to-Frame Psi Value [Btu/hr·ft·°F]	0.0065	0.0065	0.0060	0.0054

**Frame-to-Wall Psi Value** is dependent on the on-site installation condition. (See Phius Guidebook for more details.)

For vertical two-lite products, assume Lite One is on top and Lite Two is on the bottom. The sill of Lite One is the lower meeting rail. The head of Lite Two is the upper meeting rail. | 08/28/2025



**Phius Product Number:** W-102029  
**Date Last Certified:** 08/28/2025  
**THERM Files Available:** No

**Phius Certification Path:** Blue Path  
**Valid Through:** 08/24/2026  
**Air Leakage Test Data Available:** No



**PRODUCT INFORMATION**

<b>Product Name:</b> DRUTEX IGLO ENERGY Classic Tilt & Turn Over Fixed	
<b>Manufacturer:</b> DRUTEX S A	<b>Primary Frame Material:</b> Vinyl
<b>Series:</b> IGLO ENERGY Classic	<b>Fixed or Operable:</b> Combination
<b>Model:</b> IGLO ENERGY Classic Tilt & Turn over Fixed	<b>Operation Type:</b> Combination Unit
<b>Number of Lites:</b> Two-Lite	<b>Two-Lite Orientation:</b> Vertical
<b>NFRC CPD #:</b> DRU-K-6-00262-00001   <b>NFRC CPD # Lite Two:</b> DRU-K-5-00252-00001	

**IGU DETAILS**

<b>Glazing Name:</b> SGG Cool-Lite SKN176 / ARG90 / SGG PlaniClear / ARG90 / SGG PlaniTherm XN (6mm/4mm/4mm)		
<b>Glass Layers:</b> Triple	<b>Gas Fill:</b> Argon	<b>Spacer:</b> SWISSPACER ULTIMATE

**RECOMMENDED CLIMATE ZONES** (NOTE: This information is not for use in building energy models. See next section.)

Recommended Climate Zones and Whole-Window U-values by Zone, at Standard Model Size [W/m²K]										
Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
Recommended Zones	✓	✓	✓	✓	✓	✓				
U-Whole-Window	0.89	0.90	0.90	0.89	0.91	0.90	0.92	0.93	0.96	0.98
Modeled Size [W × H]	1.20 m × 3.00 m		SHGC, Whole Window: 0.19				Condensation Resistance:			

**COMPONENT-LEVEL PERFORMANCE DATA** [SI Units] | Compatible with building energy modeling tools

U-COG   Center of Glass U-Values, by Climate Zone [W/m²K]										
Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
U-COG Value	0.56	0.57	0.57	0.56	0.59	0.58	0.61	0.62	0.67	0.71
SHGC-COG   Center of Glass Solar Heat Gain Coefficient, All Climate Zones								0.31		

Frame Parameters	Upper Left Jamb	Upper Right Jamb	Head	Upper Meeting Rail
Frame Section	Left	Right	Top	Bottom
Frame Width	125 mm	125 mm	125 mm	151 mm
Frame U-Value [W/m²K]	1.33	1.33	1.30	1.30
Glazing-to-Frame Psi Value [W/mK]	0.0116	0.0116	0.01	0.0103

Frame-to-Wall Psi Value is dependent on the on-site installation condition. (See Phius Guidebook for more details.)

Frame Parameters, Lite-Two	Lower Left Jamb	Lower Right Jamb	Lower Meeting Rail	Sill
Frame Section	Left	Right	Top	Bottom
Frame Width	75 mm	75 mm	151 mm	75 mm
Frame U-Value [W/m²K]	1.30	1.30	1.30	1.22
Glazing-to-Frame Psi Value [W/mK]	0.0113	0.0113	0.0105	0.0094

Frame-to-Wall Psi Value is dependent on the on-site installation condition. (See Phius Guidebook for more details.)

For vertical two-lite products, assume Lite One is on top and Light Two is on the bottom. The sill of Lite One is the lower meeting rail. The head of Lite Two is the upper meeting rail. | 08/28/2025