



Phius Product Number: W-102104
Date Last Certified: 09/18/2024
THERM Files Available: No

Phius Certification Path: Blue Path
Valid Through: 09/18/2026
Air Leakage Test Data Available: No



PRODUCT INFORMATION

Product Name: Inline Fiberglass 400 Series Commercial Fixed	
Manufacturer: Inline Fiberglass Ltd	Primary Frame Material: Fiberglass
Series: 400 Series Commercial	Fixed or Operable: Fixed
Model: 400 Series Commercial Fixed	Operation Type: Fixed
NFRC CPD #: IFL-A-21-00211-00001	

IGU DETAILS

Glazing Name: 6MM CL ARG 366 6MM ARG 366 6MM - 1-3/4" IG		
Glass Layers: Triple	Gas Fill: Argon	Spacer: Cardinal Endur

RECOMMENDED CLIMATE ZONES (NOTE: This information is not for use in building energy models. See next section.)

Recommended Climate Zones and Whole-Window U-values by Zone, at Standard Model Size [Btu/hr·ft²·°F]										
Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
Recommended Zones	✓	✓	✓	✓	✓	✓	✓			
U-Whole-Window	0.14	0.14	0.14	0.14	0.14	0.14	0.14	0.14	0.14	0.15
Modeled Size [W×H]	47.24" × 59.06"		SHGC, Whole Window: 0.25				Condensation Resistance:			

COMPONENT-LEVEL PERFORMANCE DATA [IP Units] | Compatible with building energy modeling tools

U-COG Center of Glass U-Values, by Climate Zone [Btu/hr·ft²·°F]										
Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
U-COG Value	0.11	0.11	0.11	0.11	0.11	0.11	0.11	0.11	0.11	0.12
SHGC-COG Center of Glass Solar Heat Gain Coefficient, All Climate Zones								0.30		

Frame Parameters	Left Jamb	Right Jamb	Head	Sill
Frame Section	Left	Right	Top	Bottom
Frame Width	2.05"	2.05"	2.05"	2.05"
Frame U-Value [Btu/hr·ft²·°F]	0.27	0.27	0.26	0.26
Glazing-to-Frame Psi Value [Btu/hr·ft·°F]	0.0083	0.0083	0.0080	0.0080
Frame-to-Wall Psi Value is dependent on the on-site installation condition. (See Phius Guidebook for more details.)				



Phius Product Number: W-102104
Date Last Certified: 09/18/2024
THERM Files Available: No

Phius Certification Path: Blue Path
Valid Through: 09/18/2026
Air Leakage Test Data Available: No



PRODUCT INFORMATION

Product Name: Inline Fiberglass 400 Series Commercial Fixed	
Manufacturer: Inline Fiberglass Ltd	Primary Frame Material: Fiberglass
Series: 400 Series Commercial	Fixed or Operable: Fixed
Model: 400 Series Commercial Fixed	Operation Type: Fixed
NFRC CPD #: IFL-A-21-00211-00001	

IGU DETAILS

Glazing Name: 6MM CL ARG 366 6MM ARG 366 6MM - 1-3/4" IG		
Glass Layers: Triple	Gas Fill: Argon	Spacer: Cardinal Endur

RECOMMENDED CLIMATE ZONES (NOTE: This information is not for use in building energy models. See next section.)

Recommended Climate Zones and Whole-Window U-values by Zone, at Standard Model Size [W/m ² K]										
Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
Recommended Zones	✓	✓	✓	✓	✓	✓	✓			
U-Whole-Window	0.81	0.80	0.80	0.80	0.80	0.80	0.81	0.81	0.82	0.83
Modeled Size [W × H]	1.20 m × 1.50 m		SHGC, Whole Window: 0.25				Condensation Resistance:			

COMPONENT-LEVEL PERFORMANCE DATA [SI Units] | Compatible with building energy modeling tools

U-COG Center of Glass U-Values, by Climate Zone [W/m ² K]										
Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
U-COG Value	0.64	0.63	0.63	0.63	0.63	0.63	0.63	0.64	0.65	0.66
SHGC-COG Center of Glass Solar Heat Gain Coefficient, All Climate Zones								0.30		

Frame Parameters	Left Jamb	Right Jamb	Head	Sill
Frame Section	Left	Right	Top	Bottom
Frame Width	52 mm	52 mm	52 mm	52 mm
Frame U-Value [W/m ² K]	1.51	1.51	1.50	1.50
Glazing-to-Frame Psi Value [W/mK]	0.0145	0.0145	0.014	0.014

Frame-to-Wall Psi Value is dependent on the on-site installation condition. (See Phius Guidebook for more details.)