



Phius Product Number: W-102241
Date Last Certified: 12/11/2024
THERM Files Available: No

Phius Certification Path: Blue Path
Valid Through: 12/11/2026
Air Leakage Test Data Available: No



PRODUCT INFORMATION

Product Name: Inline Series 325 Casement

Manufacturer: Inline Fiberglass Ltd

Primary Frame Material: Fiberglass

Series: 325 Series

Fixed or Operable: Operable

Model: Series 325 Casement

Operation Type: Casement

NFRC CPD #: IFL-A-24-00242-00001

IGU DETAILS

Glazing Name: 6MM CL ARG 180 6MM ARG 180 6MM - 1 5/8" IG

Glass Layers: Triple

Gas Fill: Argon

Spacer: Cardinal Endur

RECOMMENDED CLIMATE ZONES (NOTE: This information is not for use in building energy models. See next section.)

Recommended Climate Zones and Whole-Window U-values by Zone, at Standard Model Size [Btu/hr·ft²·°F]

Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
Recommended Zones					✓	✓				
U-Whole-Window	0.19	0.19	0.19	0.19	0.19	0.19	0.19	0.19	0.19	0.19

Modeled Size [W×H] 23.62" × 59.06"

SHGC, Whole Window: 0.37

Condensation Resistance:

COMPONENT-LEVEL PERFORMANCE DATA [IP Units] | *Compatible with building energy modeling tools*

U-COG | Center of Glass U-Values, by Climate Zone [Btu/hr·ft²·°F]

Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
U-COG Value	0.14	0.14	0.14	0.14	0.14	0.14	0.14	0.14	0.14	0.14

SHGC-COG | Center of Glass Solar Heat Gain Coefficient, All Climate Zones

0.54

Frame Parameters	Left Jamb	Right Jamb	Head	Sill
Frame Section	Left	Right	Top	Bottom
Frame Width	2.83"	2.83"	2.83"	2.83"
Frame U-Value [Btu/hr·ft ² ·°F]	0.24	0.24	0.23	0.23
Glazing-to-Frame Psi Value [Btu/hr·ft·°F]	0.0134	0.0134	0.0124	0.0123

Frame-to-Wall Psi Value is dependent on the on-site installation condition. (See Phius Guidebook for more details.)



Phius Product Number: W-102241
Date Last Certified: 12/11/2024
THERM Files Available: No

Phius Certification Path: Blue Path
Valid Through: 12/11/2026
Air Leakage Test Data Available: No



PRODUCT INFORMATION

Product Name: Inline Series 325 Casement

Manufacturer: Inline Fiberglass Ltd

Primary Frame Material: Fiberglass

Series: 325 Series

Fixed or Operable: Operable

Model: Series 325 Casement

Operation Type: Casement

NFRC CPD #: IFL-A-24-00242-00001

IGU DETAILS

Glazing Name: 6MM CL ARG 180 6MM ARG 180 6MM - 1 5/8" IG

Glass Layers: Triple

Gas Fill: Argon

Spacer: Cardinal Endur

RECOMMENDED CLIMATE ZONES (NOTE: This information is not for use in building energy models. See next section.)

Recommended Climate Zones and Whole-Window U-values by Zone, at Standard Model Size [W/m²K]

Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
Recommended Zones					✓	✓				
U-Whole-Window	1.07	1.06	1.06	1.06	1.06	1.06	1.06	1.05	1.05	1.05
Modeled Size [W × H]	0.60 m × 1.50 m			SHGC, Whole Window: 0.37			Condensation Resistance:			

COMPONENT-LEVEL PERFORMANCE DATA [SI Units] | *Compatible with building energy modeling tools*

U-COG | Center of Glass U-Values, by Climate Zone [W/m²K]

Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
U-COG Value	0.80	0.79	0.79	0.79	0.78	0.79	0.78	0.78	0.77	0.78
SHGC-COG Center of Glass Solar Heat Gain Coefficient, All Climate Zones								0.54		

Frame Parameters	Left Jamb	Right Jamb	Head	Sill
Frame Section	Left	Right	Top	Bottom
Frame Width	72 mm	72 mm	72 mm	72 mm
Frame U-Value [W/m ² K]	1.38	1.38	1.33	1.33
Glazing-to-Frame Psi Value [W/mK]	0.0233	0.0233	0.0215	0.0214

Frame-to-Wall Psi Value is dependent on the on-site installation condition. (See Phius Guidebook for more details.)