



Phius Product Number: W-102654
Date Last Certified: 04/01/26
THERM Files Available: No

Phius Certification Path: Orange Path
Valid Through: 04/01/28
Air Leakage Test Data Available: No



PRODUCT INFORMATION

Product Name: Alpen Zenith ZR-9 Fixed High Profile	
Manufacturer: Alpen High Performance Products	Primary Frame Material: Fiberglass
Series: Zenith ZR-9	Fixed or Operable: Fixed
Model: Zenith ZR-9 Fixed High Profile	Operation Type: Fixed

IGU DETAILS

Glazing Name: HighGain-9 TGQ [35mm oa]		
Glass Layers: Quad	Gas Fill: Krypton	Spacer: Ködispace 4SG

RECOMMENDED CLIMATE ZONES *(NOTE: This information is not for use in building energy models. See next section.)*

Recommended Climate Zones and Whole-Window U-values by Zone, at Standard Model Size [Btu/hr·ft²·°F]										
Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
Recommended Zones						✓	✓	✓		
U-Whole-Window	0.13	0.13	0.13	0.13	0.13	0.13	0.13	0.13	0.13	0.13
Modeled Size [W×H]	47.24" × 59.06"				SHGC, Whole Window: 0.44			Condensation Resistance:		

COMPONENT-LEVEL PERFORMANCE DATA [IP Units] | Compatible with building energy modeling tools

U-COG Center of Glass U-Values, by Climate Zone [Btu/hr·ft²·°F]										
Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
U-COG Value	0.11	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10
SHGC-COG Center of Glass Solar Heat Gain Coefficient, All Climate Zones								0.55		

Frame Parameters	Left Jamb	Right Jamb	Head	Sill
	Left	Right	Top	Bottom
Frame Width	2.83"	2.83"	2.83"	2.83"
Frame U-Value [Btu/hr·ft ² ·°F]	0.15	0.15	0.15	0.15
Glazing-to-Frame Psi Value [Btu/hr·ft ² ·°F]	0.0186	0.0186	0.0184	0.0184
Frame-to-Wall Psi Value is dependent on the on-site installation condition. <i>(See Phius Guidebook for more details.)</i>				



Phius Product Number: W-102654
Date Last Certified: 04/01/26
THERM Files Available: No

Phius Certification Path: Orange Path
Valid Through: 04/01/28
Air Leakage Test Data Available: No



PRODUCT INFORMATION	
Product Name: Alpen Zenith ZR-9 Fixed High Profile	
Manufacturer: Alpen High Performance Products	Primary Frame Material: Fiberglass
Series: Zenith ZR-9	Fixed or Operable: Fixed
Model: Zenith ZR-9 Fixed High Profile	Operation Type: Fixed
IGU DETAILS	
Glazing Name: HighGain-9 TGQ [35mm oa]	
Glass Layers: Quad	Gas Fill: Krypton
Spacer: Ködispace 4SG	

RECOMMENDED CLIMATE ZONES <i>(NOTE: This information is not for use in building energy models. See next section.)</i>										
Recommended Climate Zones and Whole-Window U-values by Zone, at Standard Model Size [W/m ² K]										
Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
Recommended Zones						✓	✓	✓		
U-Whole-Window	0.74	0.73	0.73	0.73	0.73	0.73	0.72	0.72	0.71	0.72
Modeled Size [W × H]	1.20 m × 1.50 m		SHGC, Whole Window: 0.44				Condensation Resistance:			

COMPONENT-LEVEL PERFORMANCE DATA [SI Units] | Compatible with building energy modeling tools

U-COG Center of Glass U-Values, by Climate Zone [W/m ² K]										
Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
U-COG Value	0.61	0.59	0.59	0.60	0.59	0.59	0.58	0.58	0.57	0.58
SHGC-COG Center of Glass Solar Heat Gain Coefficient, All Climate Zones								0.55		

Frame Parameters	Left Jamb	Right Jamb	Head	Sill
Frame Section	Left	Right	Top	Bottom
Frame Width	72 mm	72 mm	72 mm	72 mm
Frame U-Value [W/m ² K]	0.84	0.84	0.85	0.85
Glazing-to-Frame Psi Value [W/mK]	0.0322	0.0322	0.032	0.032
Frame-to-Wall Psi Value is dependent on the on-site installation condition. <i>(See Phius Guidebook for more details.)</i>				