



Phius Product Number: W-102669
Date Last Certified: 01/26/26
THERM Files Available: No

Phius Certification Path: Blue Path
Valid Through: 04/06/28
Air Leakage Test Data Available: No



PRODUCT INFORMATION

Product Name: Harvey Axio Dual Action (VF-VF)

Manufacturer: Harvey Windows & Doors

Primary Frame Material: Vinyl

Series: Axio

Fixed or Operable: Operable

Model: Axio Dual Action (VF-VF)

Operation Type: Dual Action Tilt Turn

NFRC CPD #: HII-M-52-01750-00001

IGU DETAILS

Glazing Name: E270/Argon/E180/Argon/ i89 (6mm/6mm/6mm) 1-3/4" E

Glass Layers: Triple

Gas Fill: Argon

Spacer: Cardinal Endur

RECOMMENDED CLIMATE ZONES (NOTE: This information is not for use in building energy models. See next section.)

Recommended Climate Zones and Whole-Window U-values by Zone, at Standard Model Size [Btu/hr·ft²·°F]

Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
Recommended Zones	✓	✓	✓	✓	✓	✓	✓			
U-Whole-Window	0.14	0.14	0.14	0.14	0.14	0.14	0.14	0.14	0.14	0.15
Modeled Size [W×H]	47.24" × 59.06"		SHGC, Whole Window: 0.20				Condensation Resistance:			

COMPONENT-LEVEL PERFORMANCE DATA [IP Units] | *Compatible with building energy modeling tools*

U-COG | Center of Glass U-Values, by Climate Zone [Btu/hr·ft²·°F]

Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
U-COG Value	0.10	0.11	0.11	0.11	0.11	0.11	0.11	0.11	0.11	0.11

SHGC-COG | Center of Glass Solar Heat Gain Coefficient, All Climate Zones

0.30

Frame Parameters	Left Jamb	Right Jamb	Head	Sill
Frame Section	Left	Right	Top	Bottom
Frame Width	4.92"	4.92"	4.92"	4.92"
Frame U-Value [Btu/hr·ft ² ·°F]	0.20	0.20	0.20	0.20
Glazing-to-Frame Psi Value [Btu/hr·ft·°F]	0.0058	0.0058	0.0056	0.0054

Frame-to-Wall Psi Value is dependent on the on-site installation condition. (See Phius Guidebook for more details.)



Phius Product Number: W-102669
Date Last Certified: 01/26/26
THERM Files Available: No

Phius Certification Path: Blue Path
Valid Through: 04/06/28
Air Leakage Test Data Available: No



PRODUCT INFORMATION

Product Name: Harvey Axio Dual Action (VF-VF)

Manufacturer: Harvey Windows & Doors

Primary Frame Material: Vinyl

Series: Axio

Fixed or Operable: Operable

Model: Axio Dual Action (VF-VF)

Operation Type: Dual Action Tilt Turn

NFRC CPD #: HII-M-52-01750-00001

IGU DETAILS

Glazing Name: E270/Argon/E180/Argon/ i89 (6mm/6mm/6mm) 1-3/4" E

Glass Layers: Triple

Gas Fill: Argon

Spacer: Cardinal Endur

RECOMMENDED CLIMATE ZONES (NOTE: This information is not for use in building energy models. See next section.)

Recommended Climate Zones and Whole-Window U-values by Zone, at Standard Model Size [W/m²K]

Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
Recommended Zones	✓	✓	✓	✓	✓	✓	✓			
U-Whole-Window	0.79	0.81	0.81	0.81	0.81	0.81	0.82	0.82	0.82	0.83

Modeled Size [W × H] 1.20 m × 1.50 m

SHGC, Whole Window: 0.20

Condensation Resistance:

COMPONENT-LEVEL PERFORMANCE DATA [SI Units] | *Compatible with building energy modeling tools*

U-COG | Center of Glass U-Values, by Climate Zone [W/m²K]

Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
U-COG Value	0.56	0.60	0.60	0.60	0.61	0.61	0.61	0.61	0.62	0.63

SHGC-COG | Center of Glass Solar Heat Gain Coefficient, All Climate Zones

0.30

Frame Parameters	Left Jamb	Right Jamb	Head	Sill
Frame Section	Left	Right	Top	Bottom
Frame Width	125 mm	125 mm	125 mm	125 mm
Frame U-Value [W/m ² K]	1.16	1.16	1.15	1.12
Glazing-to-Frame Psi Value [W/mK]	0.0102	0.0102	0.0097	0.0094

Frame-to-Wall Psi Value is dependent on the on-site installation condition. (See Phius Guidebook for more details.)