



**Phius Product Number:** W-102739  
**Date Last Certified:** 06/10/26  
**THERM Files Available:** No

**Phius Certification Path:** Blue Path  
**Valid Through:** 06/10/28  
**Air Leakage Test Data Available:** No



**PRODUCT INFORMATION**

<b>Product Name:</b> Berdick 3500 Fiberglass Awning	
<b>Manufacturer:</b> Berdick Windows and Doors	<b>Primary Frame Material:</b> Fiberglass
<b>Series:</b> 3500 Series	<b>Fixed or Operable:</b> Operable
<b>Model:</b> 3500 Fiberglass Awning	<b>Operation Type:</b> Awning
<b>NFRC CPD #:</b> BMM-M-11-00461-00001	

**IGU DETAILS**

<b>Glazing Name:</b> E272 / arg90 / E180 / arg90 / i89 (6mm/6mm/6mm) 1-3/4" IG_CL		
<b>Glass Layers:</b> Triple	<b>Gas Fill:</b> Argon	<b>Spacer:</b> Cardinal Endur

**RECOMMENDED CLIMATE ZONES** (NOTE: This information is not for use in building energy models. See next section.)

Recommended Climate Zones and Whole-Window U-values by Zone, at Standard Model Size [Btu/hr·ft <sup>2</sup> ·°F]										
Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
Recommended Zones	✓	✓	✓	✓	✓	✓				
U-Whole-Window	0.17	0.18	0.18	0.18	0.18	0.18	0.18	0.18	0.18	0.18
Modeled Size [W×H]	59.06" × 23.62"		SHGC, Whole Window: 0.23				Condensation Resistance:			

**COMPONENT-LEVEL PERFORMANCE DATA [IP Units]** | Compatible with building energy modeling tools

U-COG   Center of Glass U-Values, by Climate Zone [Btu/hr·ft <sup>2</sup> ·°F]										
Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
U-COG Value	0.10	0.11	0.11	0.11	0.11	0.11	0.11	0.11	0.11	0.11
SHGC-COG   Center of Glass Solar Heat Gain Coefficient, All Climate Zones								0.34		

Frame Parameters	Left Jamb	Right Jamb	Head	Sill
<b>Frame Section</b>	<b>Left</b>	<b>Right</b>	<b>Top</b>	<b>Bottom</b>
<b>Frame Width</b>	2.91"	2.91"	2.91"	2.91"
<b>Frame U-Value</b> [Btu/hr·ft <sup>2</sup> ·°F]	0.29	0.29	0.29	0.29
<b>Glazing-to-Frame Psi Value</b> [Btu/hr·ft·°F]	0.0073	0.0073	0.0072	0.0072
<b>Frame-to-Wall Psi Value</b> is dependent on the on-site installation condition. (See Phius Guidebook for more details.)				



**Phius Product Number:** W-102739  
**Date Last Certified:** 06/10/26  
**THERM Files Available:** No

**Phius Certification Path:** Blue Path  
**Valid Through:** 06/10/28  
**Air Leakage Test Data Available:** No



**PRODUCT INFORMATION**

<b>Product Name:</b> Berdick 3500 Fiberglass Awning	
<b>Manufacturer:</b> Berdick Windows and Doors	<b>Primary Frame Material:</b> Fiberglass
<b>Series:</b> 3500 Series	<b>Fixed or Operable:</b> Operable
<b>Model:</b> 3500 Fiberglass Awning	<b>Operation Type:</b> Awning
<b>NFRC CPD #:</b> BMM-M-11-00461-00001	

**IGU DETAILS**

<b>Glazing Name:</b> E272 / arg90 / E180 / arg90 / i89 (6mm/6mm/6mm) 1-3/4" IG_CL		
<b>Glass Layers:</b> Triple	<b>Gas Fill:</b> Argon	<b>Spacer:</b> Cardinal Endur

**RECOMMENDED CLIMATE ZONES** *(NOTE: This information is not for use in building energy models. See next section.)*

<b>Recommended Climate Zones and Whole-Window U-values by Zone, at Standard Model Size [W/m<sup>2</sup>K]</b>										
Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
<b>Recommended Zones</b>	✓	✓	✓	✓	✓	✓				
<b>U-Whole-Window</b>	0.97	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.01	1.01
<b>Modeled Size [W × H]</b>	1.50 m × 0.60 m		<b>SHGC, Whole Window:</b> 0.23				<b>Condensation Resistance:</b>			

**COMPONENT-LEVEL PERFORMANCE DATA [SI Units]** | *Compatible with building energy modeling tools*

<b>U-COG   Center of Glass U-Values, by Climate Zone [W/m<sup>2</sup>K]</b>										
Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
<b>U-COG Value</b>	0.58	0.63	0.63	0.62	0.63	0.63	0.63	0.63	0.64	0.65
<b>SHGC-COG   Center of Glass Solar Heat Gain Coefficient, All Climate Zones</b>								0.34		

Frame Parameters	Left Jamb	Right Jamb	Head	Sill
Frame Section	Left	Right	Top	Bottom
<b>Frame Width</b>	74 mm	74 mm	74 mm	74 mm
<b>Frame U-Value [W/m<sup>2</sup>K]</b>	1.66	1.66	1.64	1.64
<b>Glazing-to-Frame Psi Value [W/mK]</b>	0.0127	0.0127	0.0125	0.0125

**Frame-to-Wall Psi Value** is dependent on the on-site installation condition. *(See Phius Guidebook for more details.)*