phius certified product

Phius Product Number: W-102776
Date Last Certified: 06/10/26
THERM Files Available: No

Phius Certification Path: Blue Path
Valid Through: 06/10/28
Air Leakage Test Data Available: No

PRODUCT INFORMATION

Product Name: Berdick 3500 Fiberglass LP Fixed/Picture	
Manufacturer: Berdick Windows and Doors	**Primary Frame Material:** Fiberglass
Series: 3500 Series	**Fixed or Operable:** Fixed
Model: 3500 Fiberglass LP Fixed/Picture	**Operation Type:** Fixed
NFRC CPD #: BMM-M-13-00342-00001	

IGU DETAILS

Glazing Name: E272 / arg90 / E180 / arg90 / i89 (3mm/3mm/3mm) 1-1/2" IG_CL		
Glass Layers: Triple	**Gas Fill:** Argon	**Spacer:** Cardinal Endur

RECOMMENDED CLIMATE ZONES *(NOTE: This information is not for use in building energy models. See next section.)*

Recommended Climate Zones and Whole-Window U-values by Zone, at Standard Model Size [Btu/hr•ft^2•°F]

Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
Recommended Zones				✔	✔	✔	✔			
U-Whole-Window	0.13	0.13	0.13	0.13	0.13	0.13	0.13	0.14	0.14	0.14

Modeled Size [W×H] 47.24" × 59.06" **SHGC, Whole Window:** 0.30 **Condensation Resistance:**

COMPONENT-LEVEL PERFORMANCE DATA [IP Units] | *Compatible with building energy modeling tools*

U-COG | Center of Glass U-Values, by Climate Zone [Btu/hr•ft^2•°F]

Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
U-COG Value	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.11	0.11	0.11

SHGC-COG | Center of Glass Solar Heat Gain Coefficient, All Climate Zones 0.36

Frame Parameters	*Left Jamb*	*Right Jamb*	*Head*	*Sill*
Frame Section	**Left**	**Right**	**Top**	**Bottom**
Frame Width	2.13"	2.13"	2.13"	2.13"
Frame U-Value [Btu/hr•ft^2•°F]	0.28	0.28	0.27	0.27
Glazing-to-Frame Psi Value [Btu/hr•ft•°F]	0.0046	0.0046	0.0045	0.0045

Frame-to-Wall Psi Value is dependent on the on-site installation condition. *(See Phius Guidebook for more details.)*

phius certified product

Phius Product Number: W-102776
Date Last Certified: 06/10/26
THERM Files Available: No

Phius Certification Path: Blue Path
Valid Through: 06/10/28
Air Leakage Test Data Available: No

PRODUCT INFORMATION

Product Name: Berdick 3500 Fiberglass LP Fixed/Picture	
Manufacturer: Berdick Windows and Doors	**Primary Frame Material:** Fiberglass
Series: 3500 Series	**Fixed or Operable:** Fixed
Model: 3500 Fiberglass LP Fixed/Picture	**Operation Type:** Fixed
NFRC CPD #: BMM-M-13-00342-00001	

IGU DETAILS

Glazing Name: E272 / arg90 / E180 / arg90 / i89 (3mm/3mm/3mm) 1-1/2" IG_CL		
Glass Layers: Triple	**Gas Fill:** Argon	**Spacer:** Cardinal Endur

RECOMMENDED CLIMATE ZONES *(NOTE: This information is not for use in building energy models. See next section.)*

Recommended Climate Zones and Whole-Window U-values by Zone, at Standard Model Size [W/m^{2}K]

Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
Recommended Zones				✔	✔	✔	✔			
U-Whole-Window	0.73	0.76	0.76	0.76	0.76	0.76	0.77	0.77	0.78	0.80

Modeled Size [W × H] 1.20 m × 1.50 m **SHGC, Whole Window:** 0.30 **Condensation Resistance:**

COMPONENT-LEVEL PERFORMANCE DATA [SI Units] | *Compatible with building energy modeling tools*

U-COG | Center of Glass U-Values, by Climate Zone [W/m^{2}K]

Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
U-COG Value	0.55	0.59	0.59	0.58	0.59	0.59	0.59	0.60	0.61	0.63

SHGC-COG | Center of Glass Solar Heat Gain Coefficient, All Climate Zones	0.36

Frame Parameters	*Left Jamb*	*Right Jamb*	*Head*	*Sill*
Frame Section	**Left**	**Right**	**Top**	**Bottom**
Frame Width	54 mm	54 mm	54 mm	54 mm
Frame U-Value [W/m^{2}K]	1.56	1.56	1.54	1.54
Glazing-to-Frame Psi Value [W/mK]	0.008	0.008	0.0079	0.0079

Frame-to-Wall Psi Value is dependent on the on-site installation condition. *(See Phius Guidebook for more details.)*