



**Phius Product Number:** W-102801  
**Date Last Certified:** 08/04/26  
**THERM Files Available:** No

**Phius Certification Path:** Orange Path  
**Valid Through:** 08/04/28  
**Air Leakage Test Data Available:** No



## PRODUCT INFORMATION

**Product Name:** Zola ZNC Tilt and Turn

**Manufacturer:** Zola Windows

**Primary Frame Material:** Aluminum Clad Wood

**Series:** ZNC

**Fixed or Operable:** Operable

**Model:** ZNC Tilt and Turn

**Operation Type:** Dual Action Tilt Turn

## IGU DETAILS

**Glazing Name:** 4mm CG PREM2T/18mm ARG/4mm EXTRA CLR/18mm ARG/4mm CG PREM2T [48mm OA]

**Glass Layers:** Triple

**Gas Fill:** Argon

**Spacer:** ALU-PRO MULTITECH G

## RECOMMENDED CLIMATE ZONES (NOTE: This information is not for use in building energy models. See next section.)

**Recommended Climate Zones and Whole-Window U-values by Zone, at Standard Model Size [Btu/hr·ft<sup>2</sup>·°F]**

| Climate Zone       | 0, 1, 2         | 3A   | 3B   | 3C   | 4A, 4B                   | 4C, 5C | 5A, 5B | 6                        | 7    | 8    |
|--------------------|-----------------|------|------|------|--------------------------|--------|--------|--------------------------|------|------|
| Recommended Zones  |                 |      |      |      | ✓                        | ✓      | ✓      | ✓                        |      |      |
| U-Whole-Window     | 0.12            | 0.12 | 0.12 | 0.12 | 0.12                     | 0.12   | 0.12   | 0.12                     | 0.13 | 0.13 |
| Modeled Size [W×H] | 47.24" × 59.06" |      |      |      | SHGC, Whole Window: 0.37 |        |        | Condensation Resistance: |      |      |

## COMPONENT-LEVEL PERFORMANCE DATA [IP Units] | *Compatible with building energy modeling tools*

### U-COG | Center of Glass U-Values, by Climate Zone [Btu/hr·ft<sup>2</sup>·°F]

| Climate Zone | 0, 1, 2 | 3A   | 3B   | 3C   | 4A, 4B | 4C, 5C | 5A, 5B | 6    | 7    | 8    |
|--------------|---------|------|------|------|--------|--------|--------|------|------|------|
| U-COG Value  | 0.10    | 0.10 | 0.10 | 0.10 | 0.10   | 0.10   | 0.10   | 0.10 | 0.11 | 0.12 |

### SHGC-COG | Center of Glass Solar Heat Gain Coefficient, All Climate Zones

0.54

| Frame Parameters                                                                                                    | Left Jamb | Right Jamb | Head   | Sill   |
|---------------------------------------------------------------------------------------------------------------------|-----------|------------|--------|--------|
| Frame Section                                                                                                       | Left      | Right      | Top    | Bottom |
| Frame Width                                                                                                         | 4.57"     | 4.57"      | 4.57"  | 4.57"  |
| Frame U-Value [Btu/hr·ft <sup>2</sup> ·°F]                                                                          | 0.13      | 0.13       | 0.13   | 0.13   |
| Glazing-to-Frame Psi Value [Btu/hr·ft·°F]                                                                           | 0.0134    | 0.0134     | 0.0134 | 0.0134 |
| Frame-to-Wall Psi Value is dependent on the on-site installation condition. (See Phius Guidebook for more details.) |           |            |        |        |



**Phius Product Number:** W-102801  
**Date Last Certified:** 08/04/26  
**THERM Files Available:** No

**Phius Certification Path:** Orange Path  
**Valid Through:** 08/04/28  
**Air Leakage Test Data Available:** No



## PRODUCT INFORMATION

**Product Name:** Zola ZNC Tilt and Turn

**Manufacturer:** Zola Windows

**Primary Frame Material:** Aluminum Clad Wood

**Series:** ZNC

**Fixed or Operable:** Operable

**Model:** ZNC Tilt and Turn

**Operation Type:** Dual Action Tilt Turn

## IGU DETAILS

**Glazing Name:** 4mm CG PREM2T/18mm ARG/4mm EXTRA CLR/18mm ARG/4mm CG PREM2T [48mm OA]

**Glass Layers:** Triple

**Gas Fill:** Argon

**Spacer:** ALU-PRO MULTITECH G

## RECOMMENDED CLIMATE ZONES (NOTE: This information is not for use in building energy models. See next section.)

**Recommended Climate Zones and Whole-Window U-values by Zone, at Standard Model Size [W/m<sup>2</sup>K]**

| Climate Zone         | 0, 1, 2         | 3A   | 3B                       | 3C   | 4A, 4B | 4C, 5C | 5A, 5B                   | 6    | 7    | 8    |
|----------------------|-----------------|------|--------------------------|------|--------|--------|--------------------------|------|------|------|
| Recommended Zones    |                 |      |                          |      | ✓      | ✓      | ✓                        | ✓    |      |      |
| U-Whole-Window       | 0.68            | 0.67 | 0.67                     | 0.67 | 0.67   | 0.67   | 0.69                     | 0.70 | 0.73 | 0.76 |
| Modeled Size [W × H] | 1.20 m × 1.50 m |      | SHGC, Whole Window: 0.37 |      |        |        | Condensation Resistance: |      |      |      |

## COMPONENT-LEVEL PERFORMANCE DATA [SI Units] | *Compatible with building energy modeling tools*

### U-COG | Center of Glass U-Values, by Climate Zone [W/m<sup>2</sup>K]

| Climate Zone                                                              | 0, 1, 2 | 3A   | 3B   | 3C   | 4A, 4B | 4C, 5C | 5A, 5B | 6    | 7    | 8    |
|---------------------------------------------------------------------------|---------|------|------|------|--------|--------|--------|------|------|------|
| U-COG Value                                                               | 0.56    | 0.55 | 0.55 | 0.55 | 0.55   | 0.55   | 0.57   | 0.59 | 0.64 | 0.68 |
| SHGC-COG   Center of Glass Solar Heat Gain Coefficient, All Climate Zones |         |      |      |      |        |        |        | 0.54 |      |      |

| Frame Parameters                                                                                                    | Left Jamb | Right Jamb | Head   | Sill   |
|---------------------------------------------------------------------------------------------------------------------|-----------|------------|--------|--------|
| Frame Section                                                                                                       | Left      | Right      | Top    | Bottom |
| Frame Width                                                                                                         | 116 mm    | 116 mm     | 116 mm | 116 mm |
| Frame U-Value [W/m <sup>2</sup> K]                                                                                  | 0.75      | 0.75       | 0.75   | 0.75   |
| Glazing-to-Frame Psi Value [W/mK]                                                                                   | 0.0232    | 0.0232     | 0.0232 | 0.0232 |
| Frame-to-Wall Psi Value is dependent on the on-site installation condition. (See Phius Guidebook for more details.) |           |            |        |        |